



# OLD TIMER SPECIFICATIONS

(SURFACE FINISHED)

| TEST   | TEST METHOD                              | ACTUAL VALUES                             |
|--|--|---|
| Strength   |  | 1.2mm - 1.8mm                             |
| Tanning  |  | Vegetable mimosa                          |
| Size   |  | ~ 5sqm                                    |
| Raw hide   |  | European bulls                            |
| Fastness to UV   |  | Colour changes and darkening are typical  |
| Natural characteristics  |  | Typical                                   |
| Fastness to Rubbing<br>Dry - 1000 cycles<br>Wet - 500 cycles<br>Sweat - 100 cycles | DIN EN ISO 11640                         | ≥ 4.5<br>≥ 4.5<br>≥ 4.5                   |
| Adhesion<br>Dry<br>Wet   | IVF470E                                  | ≥ 3 N/cm<br>≥ 1 N/cm                      |
| Fastness to Rubbing<br>Dry<br>Wet<br>Wet after storage in water                    | DIN 53339<br><br>Evaluation<br>DIN 54002 | 4 - 5 class<br>4 - 5 class<br>4 - 5 class |

## Additional information

The Old Timer leather is traditionally made in a German factory and are not an industrial production. Tolerances in the quality of the hides are typical. This leather is sensitive to spotting and will grow darker with age. Please allow a delivery time of 3 weeks.

## What you should know about ordering leather

Due to the beautiful natural characteristics of leather, there may be some variation in shade and texture within a hide, and between hides. Although hides are free from excessive scars, there is always some evidence of their natural origin. Size will also vary between hides, but a typical hide is between 4.5-5.5m<sup>2</sup>. Please contact us for sizes available.

Samples are a good guide to colour and finish, but you should bear in mind an exact match cannot be guaranteed.

**Email** | [sales@ukhide.co.uk](mailto:sales@ukhide.co.uk)

**Phone** | +44 (0)1932 353 338

Visit us online at

[www.ukhide.co.uk](http://www.ukhide.co.uk)

