



CHARACTERISTIC	UNIT	REQUIREMENT	TEST METHOD
Thickness	mm	1.3 ± 0.1	DIN EN ISO 2286-3
Mass per unit area	g/qm	740 ± 50	DIN EN ISO 2286-2
Tensile strength Length Across	N N	≥ 400 ≥ 200	DIN 53354
Elongation Length Across	% %	≥ 80 ≥ 180	DIN 53354
Tear strength Length Across	N N	≥ 30 ≥ 30	DIN 53356
Stitch burst strength Length Across	N N	≥ 50 ≥ 40	DIN 53506
Adhesion Length Across	N N	≥ 30 ≥ 30	DIN 53357
Light fastness	Degree	≥ 6	DIN EN ISO 105-B02
Behaviour after folding Length Across	Folds	$\geq 50,000$ $\geq 50,000$	DIN 53359 DIN 50014-23/50-2
Water resistance	cm WS	≥ 200	DIN EN 20811
Low temperature resistance	°C	-20	DIN 53361
Flammability	mm/min	≤ 100	DIN 75200/ISO 3795 MVSS 302

What you should know about ordering faux leather

Fabric width is 140cm. Roll length is 25 linear metres.

Samples are a good guide to colour and finish, but you should bear in mind an exact match cannot be guaranteed.

Email | sales@ukhide.co.uk

Phone | +44 (0)1932 353 338

Visit us online at

www.ukhide.co.uk