

| MONDIAL | Standard | Result |
|--------------------------------------------|-----------------------------------------------------------------------------------------------|----------------------------|
| Tensile test | DIN EN ISO 1421 | Excellent |
| Tear resistance | DIN 53356 in Newton | Excellent |
| Flexing endurance | DIN 53351 30,000 folds | No variation |
| Colour fastness to rubbing | DIN EN ISO 105-X12 | Excellent (highest rating) |
| Martindale abrasion resistance | DIN EN ISO 5470-2 | > 100,000 |
| Colour fastness to light exposure | DIN EN ISO 105-B02 | Excellent |
| Adhesion | IUF 470/ISO 11644 | > 2.5 N/10mm |
| Flame resistance for serial leather | DIN EN 1021 part 1 + 2; ISO 8191-1; BS 5852 source 3; California TB 117 (Draft 02/2002) | Excellent |
| All other tests can be provided on request | | |

MONDIAL

MONDIAL upholstery leather is an exclusive thick leather with a thickness of 1.6 - 1.8 mm. It is especially hard wearing and due to its embossed grain structure is a favourite for use in heavy, cube shaped seating in the domestic and commercial sectors, and also for wall panelling. MONDIAL is available in 40 colours and is suitable for both modern and classic styles.

Characteristics

MONDIAL with a thickness of 1.6 - 1.8 mm is very well suited for residential and office areas, restaurants and hotels, as well as all business areas that receive heavy traffic. A specially developed process makes it possible to finish even small amounts of MONDIAL to meet the highest standards of low flammability (IMO, BS 5852 cripp V, UNI etc).

A thin colour stabiliser provides MONDIAL with excellent abrasion resistance and the best possible fastness to light. MONDIAL has excellent tensile strength, tear and kink resistance as only Central European bull skins are used exclusively for the raw material. The average size of one skin is approximately 5.4m², which guarantees tailor made cutting results.

Care & Cleaning

MONDIAL does not require special care, however, any dirt should be removed using lukewarm water and a soft cloth. Never use any solvents, chemical cleaners or other aggressive substances.

Leather Description

- Top grain leather, thickness 1.3 - 1.4mm
- Natural enhanced grain
- Raw product: Central European heavy bull hide, average size 5.3m²
- Tanning: strong vegetable re-tanned, chrome leather
- Natural features are visible
- Slight shine, colour and structure differences are normal
- Patina and shiny spots during use are typical of the product

What you should know about ordering leather

Due to the beautiful natural characteristics of leather, there may be some variation in shade and texture within a hide, and between hides. Although hides are free from excessive scars, there is always some evidence of their natural origin. Size will also vary between hides, but a typical hide is between 4.5-5.5m². Please contact us for sizes available.

Samples are a good guide to colour and finish, but you should bear in mind an exact match cannot be guaranteed.

Email | sales@ukhide.co.uk

Phone | +44 (0)1932 353 338

Visit us online at:

www.ukhide.co.uk

