



MOUNTBATTEN SPECIFICATIONS

TEST	TEST METHOD	MEASUREMENT UNIT	RESULT
Flexing Endurance - Dry 50 Cycles	UNI EN ISO 5402		No damage
Tear Strength - Single edge tear	UNI EN ISO 3377 - 1	N	≥ 20
Burning behaviour to cigarette and match flame	BS 5852:1979 BS EN 1021 - 1 - 2 : 2006		Pass
Colour fastness to artificial light - exposition energy 16,000 kj/m ²	UNI EN ISO 105 B02 (MET.5)	Blue scale	≥ 5
Finish adhesion - Dry	UNI EN ISO 11644	N/cm	≥ 2
<i>Colour fastness to Rubbing</i> Wet - 250 cycles Dry - 500 cycles Sweat - 80 cycles	UNI EN ISO 11640 :1998 11641 pH8	Grey scale	≥ 4 ≥ 4 ≥ 4

What you should know about ordering leather

Due to the beautiful natural characteristics of leather, there may be some variation in shade and texture within a hide, and between hides. Although hides are free from excessive scars, there is always some evidence of their natural origin. Size will also vary between hides, but a typical hide is between 4.8-5.0m². Please contact us for sizes available.

Samples are a good guide to colour and finish, but you should bear in mind an exact match cannot be guaranteed.

Email | sales@ukhide.co.uk

Phone | +44 (0)1932 353 338

Visit us online at

www.ukhide.co.uk

