



# SIMPLY LEATHER SPECIFICATIONS

CHARACTERISTIC	REQUIREMENT	TEST METHOD
Thickness	0.9 - 1.0	
Light resistance	IUP 2-0 / UNI EN ISO 105B0	5 blue scale
Colour fastness to rubbing grey scale Dry Wet Alkaline	IUF 450 / UNI EN ISO 11640	500 strokes $\geq$ 4 150 strokes $\geq$ 4 80 strokes $\geq$ 4
Flexing endurance	IUP 2-0 / UNI EN ISO 5402	$\geq$ 30,000
Adhesion	IUP 470 / UNI EN ISO 11644	$\geq$ 3.5 N/cm
Tear strength	IUP 40 / UNI EN ISO 3377-1	$\geq$ 2-0 N
Flammability	UNI EN ISO 102-1-1/2 BS 5852 - 1990 Sec. 4 NI/0-1 California TB 117	OK
Average size		4.2m <sup>2</sup>
Minimum order		Half hide

Simply Leather derives from South American cattle. Due to its nature, the hides might have brandings and a hole in the neck area.

## What you should know about ordering leather

Due to the beautiful natural characteristics of leather, there may be some variation in shade and texture within a hide, and between hides. Although hides are free from excessive scars, there is always some evidence of their natural origin. Size will also vary between hides, but a typical hide is 4.2m<sup>2</sup>. Please contact us for sizes available.

Samples are a good guide to colour and finish, but you should bear in mind an exact match cannot be guaranteed.

**Email** | [sales@ukhide.co.uk](mailto:sales@ukhide.co.uk)

**Phone** | +44 (0)1932 353 338

Visit us online at

[www.ukhide.co.uk](http://www.ukhide.co.uk)

