



# Sirocco Specifications

Test	Test Method	Measurement Unit	Result
Tear strength - single edge tear	UNI EN ISO 3377-1	N	≥ 20
Colour fastness to rubbing: Dry - 500 cycles Wet - 250 cycles Perspiration - 80 cycles	UNI EN ISO 11640: 1998 11641 (pH8)	Grey scale	≥ 4 ≥ 4 ≥ 4
Flex resistance - dry @50,000 cycles	UNI EN ISO 5402		No damage*
Adhesion of finish - dry	UNI EN ISO 11644	N/cm	≥ 2
Colour fastness to artificial light Exposition energy 16,000 kj/m²	UNI EN ISO 105B02 (MET. 5)	Blue scale	≥ 5
Smoulder resistance  Fire safety - burning behaviour of cigarette and match flame (this norm refers exclusively to the combination of leather and padding)	CAL TB-117 (2013, Sec 1)  BS5852:1979 Match & Cigarette test BS EN 1021-1-2:2006 Match & Cigarette test		Pass

\*Visible to the naked eye

The Sirocco range derives from non European cattle. Due to its nature, the hides might have brandings and marks and a hole in the neck area.

It is a chrome tanned corrected grain upholstery leather suitable for domestic usage, but can be treated for contract use.

The average thickness is 0.9 - 1.1mm. Average hide size of 4.3 - 5.0 square metres.

## What you should know about ordering leather

Due to the beautiful natural characteristics of leather, there may be some variation in shade and texture within a hide, and between hides. Although hides are free from excessive scars, there is always some evidence of their natural origin. Size will also vary between hides, but a typical hide is between 4.5 - 5.5m². Please contact us for sizes available.

Samples are a good guide to colour and finish, but you should bear in mind an exact match cannot be guaranteed.